



## AM2400D™

### Air Mover

- Energy efficient 3-speed motor delivers up to 2,400 CFM
- Onboard outlet for daisy-chaining up to 3 units
- Lightweight, compact and stackable
- Optional trolley kit with wheels and retractable handle for easy transport

The powerful yet compact AM2400D™ air mover provides the power and versatility to quickly dry floors and circulate air. A 3-speed induction motor with thermal protection delivers up to 2,400 CFM air flow while minimizing energy usage. Four position settings provide flexibility for directing air movement while the built-in power outlet allows for daisy-chaining up to three units for maximum efficiency. The AM2400D, with an optional trolley kit with transport wheels and retractable handle, is lightweight and stackable, making it easy to carry, store and transport. Protected by a strong roto-molded housing, the AM2400D is robust and ready to work.



Stackable (up to 3) for easy storage.



Optional trolley kit, with transport wheels and retractable handle.



Three-speed fan with built-in power outlet.



Daisy chain up to 3 units.

**Trusted. Reliable. Efficient.**

# Clarke®

| Specifications                                                       | AM2400D™                                   |
|----------------------------------------------------------------------|--------------------------------------------|
| Model Number                                                         | 50000390                                   |
| Power Source                                                         | 120 V, 60 Hz                               |
| Operating Speeds                                                     | 1,000 / 1,200 / 1,400 RPM                  |
| Maximum Airflow                                                      | 2,000 / 2,200 / 2,400 CFM (57, 62, 68 CMM) |
| Amp Draw                                                             | 3.7 / 3.8 / 4                              |
| Motor                                                                | 1/3 hp (250 W)                             |
| Working Sound Level                                                  | 64 / 68 / 72 dB A                          |
| Power Cord with Cord Wrap                                            | 21 ft (6.5 m)                              |
| Dimensions (LxWxH)                                                   | 16 X 16 X 18 in (40.5 x 40 x 47 cm)        |
| Weight                                                               | 22 lb (10 kg)                              |
| Housing Material                                                     | Durable Roto-mold                          |
| Stackable                                                            | Yes                                        |
| Built-in Power Outlet                                                | Yes                                        |
| Trolley Kit, with Transport Wheels and Retractable Handle (optional) | V V78406 – Flexibility Trolley Kit         |

Specifications are subject to change without notice.



Optional Trolley Kit  
(part number VV78406)

### Powerful and Versatile

- Delivers up to 2,400 CFM
- Energy efficient 3-speed motor (High, Medium, Low)
- Multiple position settings for directing airflow
- Daisy chain up to 3 units for maximum efficiency

### User Friendly

- Compact and lightweight
- Stackable
- Optional trolley kit with wheels and retractable handle make it easy to transport

### Reliable

- Induction motor with thermal protection for safety and long life
- Robust roto-molded housing

# Clarke®

9435 Winnetka Avenue North  
Brooklyn Park, MN 55445  
Phone: 800.253.0367  
Fax: 800.825.2753  
www.clarkeus.com

240 Superior Boulevard  
Mississauga, Ontario, Canada L5T 2L2  
Phone: 800.668.8400  
Fax: 800.263.5111  
www.nilfisk-advance.ca